



## Curve Grease

Curve Grease is a high-quality, mixed calcium-lithium grease developed for the lubrication of curved railroad tracks. It is sprayed on the sides of the railroad tracks through stationary applicators to minimize metal-to-metal contact, reduce friction between the train wheels and the rail, and extend the life of the curved railroad tracks.

Curve Grease is manufactured with naphthenic base oils and a mixed calcium-lithium soap thickener. It is fortified with antiwear additives and graphite to provide outstanding protection for the curved rails and rail car wheel flanges exposed to heavy loads over a wide range of temperatures. It retains its fluidity at low temperatures and its consistency at high temperatures, and has excellent resistance to water washout. It adheres to the rails in wet and dry conditions.

### **Applications**

- Curved railroad tracks
- Wheel flanges of railroad cars
- Mobile and stationary equipment requiring a graphite grease

### **Features/Benefits**

- Excellent resistance to changes in consistency at high temperatures
- Adheres to metallic surfaces
- High film strength
- Excellent resistance to water washout
- Reduces friction for improved track and wheel life

**Track Grease For  
Railroad  
Applications**

### **Contact Information**

**U.S. Customer  
Service:  
1-800-822-6457**

**U.S. Technical  
Services Hot Line:  
1-800-766-0050**

**International:  
+1-832-486-3363**

**E-mail address:  
*lubricants@  
conocophillips.com***

***<http://lubricants.conocophillips.com>***

**600 N. Dairy Ashford • 2W9000 • Houston, TX 77079**



## Curve Grease

### Typical Properties

<b>NLGI Grade</b>	<b>1</b>
Thickener	Calcium-Lithium
Color	Black
Dropping Point, °C (°F)	171 (340)
Density, lbs/gal	7.62
Penetration, Worked (60 strokes), ASTM D217	325
Texture	Smooth
Graphite, wt %	12
Base Oil Properties:	
Viscosity,	
cSt @ 40°C	66
cSt @ 100°C	7.5
SUS @ 100°F	345
SUS @ 210°F	51
Viscosity Index	58
Usable Temperature Range,	
°C	4 to 116
°F	-20 to 240

### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Due to continual product research and development, the information contained herein is subject to change without notification.

Copyright © 2006 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.



CSB-07 4052072  
02/07