



## Omniguard™

Omniguard is a high-performance, multipurpose, extreme-pressure (EP), corrosion-preventive grease specially developed for use in industrial and automotive equipment operating in wet or corrosive environments. It is particularly recommended for equipment exposed to water contamination, saltwater corrosion and/or high temperatures.

Omniguard is manufactured with high-quality paraffinic base oils, calcium sulfonate thickener, antiwear additives and rust and corrosion inhibitors. It protects against rust and corrosion in high-humidity, high-temperature applications such as those found in the steel, lumber, tire manufacturing and paper industries. It has excellent load-carrying capacity, high shear stability and outstanding resistance to water washout.

Omniguard Grade No. 2 is NLGI GC-LB certified for use as a multipurpose automotive wheel bearing and chassis lubricant.

### **Applications**

- Industrial and automotive equipment operating in unfavorable conditions involving water contamination and/or high temperatures
- Plain and rolling-element bearings operating in corrosive environmental conditions
- Marine equipment, heavy mobile equipment and cables exposed to saltwater
- Paper machine wet- and dry-end bearings and hot calender stacks
- Rolling mills, hot roll tables, continuous casters, ingot buggies and slab mills
- Steel mill roller bearings, conveyors and gears
- Industrial equipment subject to high loads, high humidity and high temperatures
- Centralized lube systems and auto lubbers in service shops

### **Features/Benefits**

- Excellent oxidation resistance and thermal stability at high temperatures
- Outstanding rust and corrosion protection, including resistance to saltwater corrosion
- Excellent extreme-pressure and antiwear properties
- Outstanding resistance to water washout
- Excellent shear stability
- High dropping point (>550°F)

**Premium  
Extreme-Pressure,  
Corrosion-Preventive  
Calcium Sulfonate  
Grease**

### **Contact Information**

**U.S. Customer  
Service:  
1-800-822-6457**

**U.S. Technical  
Services Hot Line:  
1-800-766-0050**

**International:  
+1-832-486-3363**

**E-mail address:  
lubricants@  
conocophillips.com**

<http://lubricants.conocophillips.com>

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



- Light-colored, low staining
- NLGI GC-LB certified (Grade No. 2)

### Omniguard™

#### Typical Properties

NLGI Grade	1	2
Thickener	Calcium Sulfonate	Calcium Sulfonate
Color	Tan	Tan
Dropping Point, °C (°F)	300 (572)	300 (572)
Density, lbs/gal	8.29	8.29
Penetration, Worked (60 strokes), ASTM D217	325	280
Texture	Smooth	Smooth
Four-Ball EP, ASTM D2596, Weld Load, kgf	500	500
Four-Ball Wear, ASTM D2266, Scar Diameter, mm	0.39	0.39
Oxidation Stability, ASTM D942, 100 hours,		
Pressure Drop, psi (kPa)	0 (0)	0 (0)
Roll Stability, ASTM D1831, Change in Penetration, %	7	7
Rust Prevention, ASTM D1743	Pass	Pass
Shear Stability, ASTM D217, Change (100,000 strokes), %	1	1
Timken OK Load, ASTM D2509, lb	65	65
Water Washout Resistance, ASTM D1264, Weight Loss @ 175°F, %	2.81	2.81
Base Oil Properties:		
Viscosity,		
cSt @ 40°C	219	219
cSt @ 100°C	18.8	18.8
SUS @ 100°F	1,160	1,160
SUS @ 210°F	96	96
Viscosity Index	95	95
Usable Temperature Range,		
°C	-18 to 260	-18 to 260
°F	0 to 500	0 to 500

### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Due to continual product research and development, the information contained herein is subject to change without notification.

Copyright © 2006 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.