



## GT-1 Full Synthetic Motor Oil with Liquid Titanium

Kendall GT-1 Full Synthetic Motor Oil with Liquid Titanium –

Kendall GT-1 Full Synthetic Motor Oil with Liquid Titanium,

Kendall GT-1 Full Synthetic Motor Oil with Liquid Titanium

GF-4.

IL SAC

•  
• OEM SAE 0W-20 5W-20

Kendall GT-1 Full Synthetic Motor Oil with Liquid Titanium

- API Service SM, SL, CF (SM, SL only for SAE 0W-20)
- Energy Conserving, ILSAC GF-4
- Chrysler MS-6395Q (SAE 5W-20, 5W-30, 10W-30)
- Ford WSS-M2C930-A (SAE 5W-20), WSS-M2C929-A (SAE 5W-30), WSS-M2C205-A (SAE 10W-30)
- GM6094M (SAE 5W-20, 5W-30, 10W-30)

Customer Service  
Number:

1-800-368-7128

Technical

Hot Line:

1-800-368-1267

E-mail address:

*kendallmotoroil@  
conocophillips.com*

www.us-

packaging.com

E-mail: info@us-

packaging.com

Tel: +7-4232-44-5270

ILSAC GF -4

**GT-1 Full Synthetic Motor Oil with Liquid Titanium**

SAE	0W-20	5W-20	5W-30	10W-30
@ 60°F	0.851	0.852	0.852	0.854
/ @ 60°F	7.09	7.09	7.10	7.11
, ASTM D1500	3.0	3.0	3.0	3.0
(COC), °C (°F)	229 (444)	229 (444)	235 (455)	232 (450)
, °C (°F)	<-45 (<-49)	<-45 (<-49)	<-45 (<-49)	<-45 (<-49)
cSt @ 40°C	47.2	45.9	60.0	63.0
cSt @ 100°C	8.7	8.3	10.5	10.4
, cP	168	159	166	154
, cP	6.000	4.000	4.250	3.150
@ (°C)	(-35)	(-30)	(-30)	(-25)
, cP @ 150°C	2.7	2.7	3.0	3.1
, ASTM D874, %	0.97	0.97	0.97	0.97
(TBN), ASTM D2896	8.1	8.1	8.1	8.1
, %	0.077	0.077	0.077	0.077
, %	0.010	0.010	0.010	0.010
, %	0.086	0.086	0.086	0.086

<http://w3.conocophillips.com/NetMSDS>